

Viking's Drain and Odor Control Systems

Dispensing systems for grease-digesting chemicals (bacteria, enzyme, solvent) and odor suppression chemicals

Viking Injector is leading the industry with field-proven drain and odor control chemical dispensing systems. Viking's Pro Series Dispensers are known for their reliability and durability in the field and are backed by a solid two-year warranty. The 110-Volt Pro Drain Chief is the best-known dispenser in the industry for grease trap maintenance. The Pro Battery Drain Chief uses two alkaline lantern batteries to dispense where outlets are not available. Viking's Pro Scentnal is used for odor suppression around trash chutes, compactors, dumpsters, and anywhere else bad odors need to be controlled.

Common Applications

Grease trap and drain maintenance for almost any location and odor control for trash chutes and dumpsters. Also: lift stations, waste processing, water treatment, and other situations where daily chemical injection is required. Call for feasibility of other applications.

Pro Drain Chief
Control System for
Dispensing Grease-Digesting
Chemicals or Enzymes



**Pro Battery Drain Chief at
work in a hospital kitchen**

Viking
INJECTOR


Visit us online at
www.viking-injector.com

Viking's Drain and Odor Control Systems



Pro Battery Drain Chief

Control System for Dispensing Grease-Digesting Chemicals or Enzymes in Remote Locations



Pro Battery Drain Chief

Digital Timer Provides Easy Programming and Battery Back-Up Maintains Program During Battery Change



Pro Battery Drain Chief at work in a school kitchen

Viking Injector Dispensing Systems Sales Sheet

System	Dimensions	Pump Output Per Minute	Minimum Quantity Per On Period	Maximum Quantity Per 24 Hours	Number of Feed Times Per Hour	Maximum Number of Feed Times Per 24-Hour Period	Timer Features	Power Source	Installation Hardware Included	Options	Applications
Pro Drain Chief Low Speed	7"H x 7"W x 6-1/2"D	4 ounces (116ml)	.26 ounces (7.7ml)	16.5 gallons (61.2 liters)	2	48	Potential of 48 cycles per 24-hr. period	110-volt outlet (230 VAC 50 Hz model available)	Yes	Viton tube, leg lift kit, private label, 230 VAC 50 Hz operation	Grease trap & drain maintenance-lift stations, waste-processing, water treatment, etc.
Pro Drain Chief High Speed	7"H x 7"W x 6-1/2"D	18 ounces (522ml)	1.2 ounces (34.8ml)	74 gallons (275.6 liters)	2	48	Potential of 48 cycles per 24-hr. period	110-volt outlet (230 VAC 50 Hz model available)	Yes	Viton tube, leg lift kit, private label, 230 VAC 50 Hz operation	Grease trap & drain maintenance-lift stations, waste-processing, water treatment, etc.
Pro Scental	7"H x 7"W x 6-1/2"D	17 ounces (493ml)	1.13 ounces (32.9ml)	70 gallons (260.4 liters)	2	48	Potential of 48 cycles per 24-hr. period	110-volt outlet (230 VAC 50 Hz model available)	Yes	Viton tube, leg lift kit, private label, 230 VAC 50 Hz operation	Trash chutes, compactors, dumpsters, and other locations where odor suppression is needed.
Pro Battery Drain Chief	7"H x 7"W x 6-1/2"D	4 ounces (116ml) at 12 volts DC*	4 ounces (116ml) at 12 volts DC*	**	8, if necessary	8	Digital timer has its own battery to retain program-8 on times per 24-hr. period, run time is programmable-minimum run time for each period is 1 minute	Two 6-volt spring top lantern batteries or 110-volt plug-in adapter (not included)	Yes***	Batteries, 110-volt AC to 12-volt DC plug-in adapter, leg lift kit, metal lock, private label	Remote locations where an outlet may not be available. Grease trap & drain maintenance-lift stations, waste processing, water treatment, etc.

* Output will diminish with battery operation as battery voltage drops from 12 volts.

** Run time is programmed through the timer clock; any amount of run time is available for any given on period.

*** Batteries/plug-in adapter not included. Unit uses two 6-volt alkaline spring-top batteries.

Note: All pump outputs listed are based on water. Product viscosity and length and rise of run will reduce actual output.

On all models except Battery Drain Chief, minimum run time per "on" period is 4 seconds; maximum run time is 10 minutes.

Call us regarding unusual applications.

